

WiFio-404

16 Channels Relay Output Module

(Dielectric Strength)



Main Features

- ① 16-Ch Relay Output
- ① Dielectric Strength 3KV
- ① WiFi / LAN connection
- ① Operate Time 10ms Max
- ① Release Time 5ms Max

PRELIMINARY



Introduction

The WiFio-404 is a 16 Channels Relay Output Module with Dielectric Strength of WiFio Series. The WiFio Series is an Ethernet-based wireless IIoT device, which has integrated the IoT data acquisition, processing, and publishing functions altogether. The WiFio Series also provide WiFi and LAN connection for users when establishing networks.

WiFio Series Modules include Analog, Digital, and Relay modules which also with 6~32 channels.

Model Name	WiFio-404
General	
Power Input	10~60VDC
Power Consumption	200mA@24V
Temperature-Operating	-25 ~ 70 °C
Temperature-Storage	-30 ~ 75 °C
Humidity	5 ~ 95 %
Dimensions	120.1 mm*94.4 mm*121.1mm
Weight	360g (Average)
LED Indicators	System,Config,WLAN
WiFio-Master	
LAN Connection	1 x RJ45
Transmission Speed	10/100 Base-TX Ethernet

WiFi Connection	IEEE 802.11/b/g/n Internal built-in ceramic antenna and optional external antenna via I-PEX connector
WiFi Mode	STAP/AP Configurable TX Power Support External Antenna
Modbus Connector	2 serial port both support baud rate up 115200bps 1 DIN-rail port to connect Wolf Series seamlessly
Modbus Interface	1 isolated DB9 type port to support RS232/422/485 by user configurable.
Modbus RTU Modes	Master/Slave Mode manage up to 8 devices
Modbus TCP Modes	Master/Slave Mode
Modbus Function Codes	Full support Modbus/TCP/RTU protocol and depends on equipped devices
Modbus Baud Rate	1.2K~115.2K Baud Rate
http Server	Support http and https
SSH	Secure Session
DHCP	DHCP Client to Obtain IP Address
Supported Browsers	Internet Explorer 8/9/10 and, Mozilla Firefox 24, Safari 5.1.7, Chrome 31, Oper 16.0, with at least 3 simultaneous connections.
Mounting	DIN EN 60715
Safety	FCC/CE/RoHS
WiFi-Slave	
Watchdog Timer	System (1.6 second Fixed) Communication (Programmable)
Interface	RS-485
Communication Protocol	Modbus/RTU
Communication Speed	Serial: From 1200 to 115.2k bps
Communication Distance	Serial: 1.2km
Isolation Protection	2500 or 3000 VDC
I/O Specifications	
Channels	16
Power Consumption	3.8W @ 24V
Relay Output Channels	8 Form A, 8 Form C
Contact Rating	5A 250VAC/30VDC
Dielectric Strength	3KV

Operate Time	10ms Max.
Release Time	5ms Max.
Electrical Endurance	1x105ops@3A 250VAC/30VDC

【WiFio-404】 Terminal Assignment

